


# Fast Ethernet POF 1x9 Transceiver Module

## Datasheet: 2.2POF650HPS5.0

### Description:

The transceiver module comprises a standard 1x9 electrical interface suitable for many Fast Ethernet network components like media converters and switches. Standard POF (NA = 0.5) duplex cable is plugged in without cable connector. All POF cables with a cable outside diameter of 2.2mm fit to the adapter.

The transceiver module requires a 5.0V power supply. The receiver unit comprises a novel high pass receiver electronics that compensates the high dispersion of standard POF. The use of low NA POF (NA = 0.3) is possible, too. The transmitter center wavelength at room temperature is 647nm. It shifts to the POF attenuation minimum at 650nm with elevated temperatures.



### Pinout:

1 = Gnd	6 = TX Vcc
2 = Data Out	7 = !Data In!
3 = !Data Out!	8 = Data In
4 = Signal-Detect	9 = Gnd
5 = RX Vcc	



### Applications:

The transceiver module is applied in Fast Ethernet over POF systems applications like:

- Industrial communication systems
- LAN-networks
- Inhouse networks

### Technical Data:

typ. Average output power	typ.center wavelent	datarate	typ. Link distance	typ. receiver sensitivity	system application	input optical power maximum
-3dBm	645nm	125Mbit/s	1...75m	-20dBm	100BaseFX	0dBm

power supply voltage	supply current TX (pin 6)	supply current RX (pin 5)	diff. data input (pins 2+3)	diff. data output (pins 7+8)	operating temperature
5V ± 5%	150mA	75mA	PECL	PECL	-20...70°C

### Notes:

- Power supply lines require external filter components.
- Typical values are typical data @ 25°C with standard POF, usually also available over operating temperature range.
- Differential data input and differential data output (PECL) require external components for line termination and level adjustment.
- Signal-detect output level (PECL) is generated inside the module.
- Receiver sensitivity depends on signal quality with respect to dispersion and signal optical power. The given sensitivity applies for a signal attenuated and dispersed by full length POF only.
- For additional information on required external components, e.g. level translation to LVPECL, custom POF-connectors or other feasible modifications please contact DieMount GmbH.

**DieMount GmbH**



Konrad-Zuse-Straße 14, 99099 Erfurt

www.diemount.com, phone: +49 (0) 361 6539280, fax: +49 (0) 361 6539289, E-mail: info@diemount.com